

In the claims:

1. (currently amended) A method for manufacturing multiphase windings (32) of an electric machine with the following process steps:

a) deforming a cross section of elongated wire elements (7, 11, 12) by stamping a cross-sectional profile (13) of said wire elements to increase a slot space factor;

b) loading offsetting dies (14, 26) with some of the stamped wire elements (7) to constitute a winding (32), with other of the stamped wire elements (11) to constitute an integrated star point (21), and with further of the stamped wire elements (12) for supplying current to the winding (32) and ~~rotating said stamped wire elements (7) counter to one another in a circumferential direction which is transverse to a longitudinal direction of the stamped wire elements, so that the stamped wire elements are disposed at right angles to one another and radially inward to form an integrated star point (21);~~

c) forming a winding head with an integrated star point by simultaneously moving, by means of the offsetting dies, two legs of the winding constituting some stamped wire elements which are U-shaped in a circumferential direction that is transverse to a longitudinal

direction of the stamped wire elements, arranging the other star point
constituting stamped wire elements so that their bent ends are
orientated radially inwards toward one another in a shape of a star,
and arranging the further current supplying stamped wire elements on
an outside of the winding head opposite to the other star point
constituting stamped wire elements~~offsetting the stamped wire~~
~~elements (7, 11, 12) by rotating ends of the stamped wire elements~~
~~counter to one another using further offsetting dies (14, 26), and~~
~~offsetting the ends of the stamped wire elements so that the integrated~~
~~star point (21) is maintained, wherein when said ends of the stamped~~
~~wire elements are offset, a winding head is formed, and wherein~~
~~manufacture of the integrated star point takes place simultaneously in~~
~~the same process step as the offsetting of the stamped wire elements;~~

d) connecting the bent radial, inward-oriented ends of
the other stamped wire elements with a connecting ring, whereby an
electrical contacting of the integrated star point is completed, and
wherein the entire connecting ring (40) is disposed radially inward on
an inside (41) of at~~the~~ finished winding head (20), ~~wherein said winding~~
~~head (20) includes the ends of the stamped wire elements; and~~

e) ~~carrying out on an interconnection point end (23) of a~~
~~winding (32), an automatable contacting (30) of the integrated star~~

point (21) by a process selected from the group consisting of resistance welding, laser welding, electron welding, soldering process, hot pressing and cold pressing.

2. (currently amended) The method as recited in claim 1, wherein said stamping includes stamping a cross-sectional profile in a wedge shape (13) onto the wire elements (7, 11, 12).

3. (currently amended) The method as recited in claim 1, wherein said stamping includes stamping an oval or circular cross-sectional profile onto the wire elements (7, 11, 12).

4. (currently amended) The method as recited in claim 1, further comprising loading the offsetting dies (14, 26) with the stamped wire elements (7, 11, 12) in such a way that the other wire elements (11) that constitute the integrated star point (21) are offset from one another by an angle of 120°.

5. (currently amended) The method as recited in claim 1, further comprising shaping the winding head (20) by means of an offsetting of the offsetting dies (14, 26).

6. (currently amended) The method as recited in claim 1, further comprising producing a wire cage (22) and attaching it to a laminated core (24).

7. (currently amended) The method as recited in claim 6, further comprising providing the laminated core (24) with an insulation (31) in an attachment region of ~~a~~the wire basketcage (22).

8. (currently amended) The method as recited in claim 1, further comprising contacting ~~some~~ of the some stamped wire elements (7) to one another on contacting end (25) of the winding (32).

Claim 9 cancelled.

10. (currently amended) The method as recited in claim 1, wherein the ~~automatable~~ contacting (30) is carried out by ~~connecting the wire elements (11) to the connecting ring (40) to form the integrated star point (21), which~~connecting includes using the ring that has recesses (45) or is encompassed by a ring material whose loops (44) encompass the other wire elements (11) to form the integrated star point (21).

Claims 11 -13 canceled.